

**Collector Server (RCS-COLL)**

- Power Edge R610 rack chassis or equivalent
- Intel Xeon E5530 processor (2.26GHz, cache 8MB, 5.86GT/s QPI, Turbo)
- 8GB Memory for 1 CPU
- 2 x 73GB SAS 15.000rpm 2.5" hot-plug disk for operating system in RAID 1
- 2 x PSU 717W
- Dual Embedded Broadcom 5709 2 ports GbE LOM-TCP/IP Engine (4 ports TOE) iSCSI offload
- iDRAC6 Enterprise
- dongle key

**Database Server (RCS-DB)**

- Power Edge R610 rack chassis
- Intel Xeon X5647 processor (2.93 GHz, cache 12MB, 1333 MHz Mem)
- 64GB Memory for 1CPU 1333 MHz)
- H700 1GB PERC RAID 1
- 2 x 900GB SAS 10K
- 2 x 1TB SATA 7200rpm
- 2 x PSU 717W
- Dual Embedded Broadcom 5709 2 ports GbE LOM-TCP/IP Engine (4 ports TOE iSCSI offload
- iDRAC6 Enterprise
- dongle key

**USER CLIENT's**

- Dell Latitude E6400 or equivalent
- 4 GB RAM
- DVD Burner
- Windows 7 User Client lisenziyalar