



Especificaciones

Equipos a Cotizar PN

**14 Enero 2015
Santo Domingo, DN
República Dominicana**

RCS Master Node and RCS Shard

DELL PowerEdge R530 Server **(Sustituye al R720)**



PowerEdge R430/R530 Motherboard

ProSupport: Next Business Day On-Site Service After Problem Diagnosis, 3 Year

ProSupport: 7X24 HW / SW Tech Support and Assistance, 3 Year

Dell Limited Hardware Warranty Plus Service, Initial Year

Dell Proactive Systems Management - Declined - www.dell.com/Proactive

SHIP,R530,NO,NO,DAO

Riser

On-Board LOM 1GBE (Dual Port for Towers, Quad Port for Racks)

iDRAC Port Card

iDRAC8 Enterprise, integrated Dell Remote Access Controller, Enterprise

OpenManage Essentials, Server Configuration Management

3.5" Chassis with up to 8 Hard Drives

Bezel

Performance BIOS Settings

RAID 1+RAID 10 for H330/H730/H730P (4 + 6-11 HDDs or SSDs)

PERC H730 Integrated RAID Controller, 1GB Cache

Intel Xeon E5-2660 v3 2.6GHz,25M Cache,9.60GT/s QPI,Turbo,HT,10C/20T (105W)

Max Mem 2133MHz

Upgrade to Two Intel Xeon E5-2660 v3 2.6GHz,25M Cache,9.60GT/s

QPI,Turbo,HT,10C/20T (105W)

96GB RDIMM, 2133MT/s, Dual Rank, x8 Data Width 2133MT/s RDIMMs

Performance Optimized

(2) 300GB 15K RPM SAS 6Gbps 2.5in Hot-plug Hard Drive,3.5in HYB CARR,13G

(4) 600GB 10K RPM SAS 6Gbps 2.5in Hot-plug Hard Drive,3.5in HYB CARR,13G

Electronic System Documentation and OpenManage DVD Kit for R530

DVD+/-RW, SATA, Internal

ReadyRails Sliding Rails With Cable Management Arm

Dual, Hot-plug, Redundant Power Supply (1+1), 750W

NEMA 5-15P to C13 Wall Plug, 125 Volt, 15 AMP, 10 Feet (3m), Power Cord, North America

Windows Server 2008 R2 SP1 Enterprise Edition 64 Bit (English)

No Operating System

No Media Required

Up to 135W Heatsink for PowerEdge R530

Up to 135W Heatsink for PowerEdge R530

RCS Collector

DELL PowerEdge R320, Intel Xeon E-24XX v2 Processors **(Sustituye al R210 II)**



PowerEdge R320 Motherboard, TPM

ProSupport: Next Business Day On-Site Service After Problem Diagnosis,Initial Year

ProSupport: Next Business Day On-Site Service After Problem Diagnosis,2 Year
Extended

ProSupport Non-Mission Critical: 7X24 HW / SW Tech Support and Assistance,3 Year

Dell Limited Hardware Warranty Plus Service,Initial Year

Dell Limited Hardware Warranty Plus Service,Extended Year(s)

On-Board LOM 1GBE (Dual Port for Racks and Towers, Quad Port for Blades)

Broadcom 5720 DP 1Gb Network Interface Card, Low Profile

iDRAC Port Card

iDRAC7 Enterprise

Chassis with up to 4, 3.5" or 2.5" Hot Plug Hard Drives

SAS Cable for 3.5" in Hot Plug Chassis

Bezel-4/8 Drive Chassis

RAID 1 for H710/H310 (2 HDDs)

PERC H310 Integrated RAID Controller

Heat Sink,PowerEdge

Intel Xeon E5-1410 v2 2.80GHz, 10M Cache, Turbo, 4C, 80W, Max Mem 1333MHz

16GB RDIMM, 1600MT/s, Low Volt, Single Rank, x4 Data Width 1600MT/s RDIMMS

Performance Optimized

(2) 300GB 15K RPM SAS 6Gbps 3.5in Hot-plug Hard Drive

Electronic System Documentation and OpenManage DVD Kit for R320

DVD+/-RW, SATA, INTERNAL

ReadyRails Sliding Rails With Cable Management Arm

Dual Hot Plug Power Supplies 350W

Power Distribution Board for Hot Plug Power Supplies

Power Cord, NEMA 5-15P to C13, 15 amp, wall plug, 10 feet / 3 meter

Windows Server 2008 R2 SP1 Enterprise Edition 64 Bit (English)

No Operating System

No Media Required

RCS Anonymizer

Linode Manager

ht_galileo my profile log out

Linodes NodeBalancers Longview DNS Manager Account Support Documentation Community

| Linode | Status | Plan | IP | Location | Backups | Options |
|--------------|---------------|-------------|-----------------|---------------------|-------------|--------------------|
| linode814997 | Brand New | Linode 1024 | 104.237.136.190 | Dallas, TX, USA | No - Enable | Dashboard Remove |
| linode815409 | Brand New | Linode 1024 | 212.71.237.194 | London, England, UK | No - Enable | Dashboard Remove |
| linode815412 | Being Created | Linode 1024 | 173.255.242.76 | Fremont, CA, USA | No - Enable | Dashboard Remove |

Manage Images | Manage StackScripts | Add a Linode

This Month's Network Transfer Pool

100% Remaining

0GB Used, 3716GB Remaining, 3716GB Quota
Your transfer is prorated and will reset next month

Linode 1GB

\$.015/hr
(\$10/mo)

- 1 GB RAM
- 1 CPU Core
- 24 GB SSD Storage
- 2 TB Transfer
- 40 Gbit Network In
- 125 Mbit Network Out

BACKUP

DELL PowerVault MD3200i, 1G iSCSI



Ship Group,MD3200I,Dell Americas Organization
PowerVault MD32xxI 4G Cache Controller
PowerVault MD32xxI 4G Cache Controller
Bezel Option, MD3200i
ReadyRails II Static Rails for 4-post Racks
ProSupport Non-Mission Critical: 7x24 HW / SW Tech Support and Assistance 3 Year
Dell Hardware Limited Warranty Initial Year
Dell Hardware Limited Warranty Extended Year(s)
ProSupport: Next Business Day On-Site Service After Problem Diagnosis,Initial Year
ProSupport: Next Business Day On-Site Service After Problem Diagnosis,2 Year
Extended
Remote Implementation of a Dell PowerVault MD3xxx Series Array
Power Supply, AC 600W, Redundant
Power Cord, NEMA 5-15P to C13, 15 amp, wall plug, 6 feet / 2 meter
Power Cord, NEMA 5-15P to C13, 15 amp, wall plug, 6 feet / 2 meter
No Additional Software
64GB RDIMM, 1600MT/s, Low Volt, Single Rank, x4 Data Width 1600MT/s RDIMMS
(6) 1TB 7.2K RPM Near-Line SAS 6Gbps 3.5in Hot-plug Hard Drive

(6) Hard Drive Filler, Single Blank

RCS Console

DELL Latitude 15 5000 Series



Intel Core i5-4310U Processor Base, Integrated Graphics, Express Card Reader

4th Gen Intel Core i5-4310U Processor (2.0 GHz, 3M Cache, Dual Core)

8GB Dual Channel DDR3L 1600MHz (4GBx2)

500GB (5.400 Rpm) Serial ATA Hard Drive

15.6" HD (1366x768) Wide View Anti-Glare WLED-backlit

Internal English Single Pointing Keyboard

Intel Integrated HD Graphics 4400

8X DVD+/-RW Media Bay Drive

Dell Wireless 1506 802.11g/n Single Band Wi-Fi Half Mini Card

Light Sensitive Webcam and Noise Cancelling Digital Array Mic

Windows 8.1 Pro 64-bit English

Windows 8.1 DVD OS Recovery(English)

6-cell (65Wh) Lithium Ion battery with ExpressCharge

65W AC Adapter, 3-pin

Dell Backup and Recovery Basic

Resource DVD

Energy Star 6.0

Latitude 15 5000 Software Drivers

Waves Maxx Audio Royalty

Dell 15.6 inch Urban 2.0 Topload

GARANTIA DE FABRICA DE TRES AÑOS EN PIEZAS Y SERVICIOS:

NBD On-Site Service 2 Years Extended

NBD On-Site Service Initial Year

Dell Limited Hardware Warranty Plus Service Extended Year

Dell Limited Hardware Warranty Plus Service Initial Year

DELL PowerConnect 2824, 24 1GbE 2 Ports with SFP option, Web Managed



Dell Hardware Limited Warranty Initial Year
Lifetime Limited Hardware Warranty with Basic Hardware Service Next Business Day
Parts Only on Your PowerConnect Switch
Basic: Business Hours (5X10) Next Business Day On Site Hardware Limited Warranty
Repair Initial Year

Tripp Lite SR42UB 42U Rack Enclosure Server Cabinet Doors and Sides

- SmartRack enclosures are designed for secure, high density server and networking applications in IT environments.
- 42U Smart Rack enclosure with doors and side panels
- Adjustable mounting rails with easy-view depth index and toolless mounting slots for PDUs and vertical cable managers. Locking, removable, reversible front and rear doors
- Weight rating of 3000 lb stationary and 2250 lb rolling

Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) compliance



APC Smart-UPS SMT3000 2700W/3000VA 120V LCD UPS System



- Output Power Capacity: 2700 Watts/3000 VA
- Nominal Output Voltage: 120V
- Output Frequency (sync to mains): 47~53Hz for 50Hz nominal, 57~63Hz for 60Hz nominal
- Waveform Type: Sine wave
- Typical recharge time: 3 hours
- Alpha/Numeric Lcd Display High-Efficiency Green Mode

Avocent ECS17KMM8P-001 Rackmount LCD. 1U 17IN LCD CONSOLE



Avocent ECS17KMM8P-001 Rackmount LCD. 1U SINGLE RAIL
17IN LCD CONSOLE W/PS2 TRACKBALL KEYB/PRE-MNT AV3008
RACK-C. Built-in Digital KVM Switch - 8 Computer(s) - 17" Active
Matrix TFT LCD - 8 x RJ-45 Keyboard/Mouse/Video - 1U Height

SonicWALL NSA 3600 Network Security Appliance



| | |
|--|-------------------------------------|
| Operating system | SonicOS 6.2 |
| Security Processor | 6x 800 MHz |
| Memory (RAM) | 2.0 GB |
| 10 GbE SFP+ interfaces | 2 |
| 1 GbE SFP interfaces | 4 |
| 1 GbE Copper interfaces | 12 |
| 1 GbE Copper Management interfaces | 1 |
| Expansion | Expansion Slot (Rear), SD Card, USB |
| Firewall inspection throughput ¹ | 3.4 Gbps |
| Full DPI throughput ² | 500 Mbps |
| Application inspection throughput ² | 1.1 Gbps |
| IPS throughput ² | 1.1 Gbps |
| Anti-malware inspection throughput ² | 600 Mbps |
| IMIX throughput ³ | 900 Mbps |
| SSL Inspection and Decryption (DPI SSL) ² | 300 Mbps |
| VPN throughput ³ | 1.5 Gbps |
| Connections per second | 20,000/sec |
| Maximum connections (SPI) | 325,000 |
| Maximum connections (DPI) | 175,000 |
| Single Sign On (SSO) Users | 500 |
| VLAN interfaces | 50 |
| SonicPoints supported (Maximum) | 48 |