

SOCCERPRO 100 60

ES2360T

Product characteristics			
Pile height	mm	60	+/- 1 mm
Total length of tuft pile	mm	126	+/- 2 mm
Gauge		3/4	
Production method (DIN 61151)		Tufted	
Stitch rate per 10 cm.	nr	16,50	+/- 1 nr
Stitch rate per m2 approx.	nr	8.700	
Total weight	gr/m2	2.450	+/- 5 %
Perforation diameter	mm	5	+/- 1 mm
Number of perforations	nr/m2	90	
Water permeability (EN12616-requirements>360l/h)		>360 l/h	

Yarn characteristics			
Decitex	dtex	11.900	+/- 5 %
Composition		100% polyethylene	
Thickness	micron	100	+/- 6 %
Type		Straight fibrillated	
Colour		Green	
Total yarn weight	gr/m2	1.340	

Backing characteristics			
Primary backing		Polypropylene/fleese	
Primary backing weight	gr/m2	160	+/- 8 %
Backing		Latex	
Backing weight	gr/m2	950	+/-10 %

Dimensions			
Rolls length	mt	40,00 or upon request	+/- 1 %
Rolls width	cm	410	+/- 2 cm

Recommended usage	Soccer
-------------------	--------

The technical specification and the quantities of the infill materials to be used for the "systems" tested according to the different International Federation can be required to our technical office.

Limonta Sport Spa, in accordance with its policy of development, reserve the right to alter above specifications without prior notice.

The recommended quantities of the infill materials can be varied according to their characteristics. We suggest to check them always by preliminary tests.

In the case that it is necessary to respect specific conditions to obtain certifications required by Sport Federations, please contact our technical department to define the types and quantities of infill materials.